

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking**1.1 Product Identifier**

AC•Tech OBS-C, Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Chemical product for construction and industry

1.3 Details of the supplier of the safety data sheet

Manufacturer:	Allied Construction Technologies, Inc. 3302 Croft Street Norfolk, VA 23513	Phone:(757)-855-5100 Email: Team@actechperforms.com
Emergency Phone:	US & Canada Infotrac: (800) 535-5053 (Contract #104212)	International Infotrac: 1-352-323-3500

SECTION 2: Hazards Identification**2.1 Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Indications of danger: C - Corrosive, Xn - Harmful

R phrases:

Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory/skin sensitization: Skin Sens. 1A

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful if swallowed or if in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2 Label Elements**Hazardous components which must be listed on the label**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

2,4,6-Tris-(dimethylaminomethyl)phenol

benzyl alcohol

Signal word: Danger

Pictograms: GHS05-GHS07



Hazard statements

H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

NFPA and HMIS Rating

NFPA Rating	Health: 2*	Fire: 2	Reactivity: 0
HMIS Rating	Health: 2	Flammability: 2	Physical Hazard: 0

SECTION 3: Composition/Information on Ingredients

3.1 Mixtures

Hazardous Components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	50 - < 75 %
2855-13-2	C - Corrosive, Xn - Harmful R21/22-34-43-52-53 Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Chronic 3; H302 H312 H314 H318 H317 H412	
01-2119514687-32		
920-901-0	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	10 - < 25 %
	Xn - Harmful R65-66	
	Asp. Tox. 1; H304 EUH066	
01-2119456810-40		
202-859-9	benzyl alcohol	10 - < 25 %
100-51-6	Xn - Harmful R20/22	
603-057-00-5	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H302 H332 H319	
01-2119492630-38		
202-013-9	2,4,6-Tris-(dimethylaminomethyl)phenol	1 - < 5 %
90-72-2	C - Corrosive R34-52-53 Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H314 H317 H412	

For Full text R-,H- and EUH-phrases: see section 16.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

General Information

Change contaminated clothing. If you feel unwell due to accidental exposure, seek medical attention immediately.
(show MSDS if possible)

After inhalation

Move to fresh air and keep warm and rest.

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious) . Sip water. Do not induce vomiting. Immediately get medical attention.

SECTION 5: Firefighting Measures

5.1 Extinguishing media

Suitable extinguishing media

- alcohol resistant foam.
- Water spray.
- Carbon dioxide (CO₂).
- dry extinguishing powder.

Unsuitable extinguishing media

- High power water jet.

5.2 Special hazards arising from the substance or mixture

Can be released in case of fire:

- Carbon monoxide
- Carbon dioxide
- Nitrogen oxides (NO_x).

5.3 Advise for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment. See protective measures under point 7 and 8. Provide adequate ventilation.

6.2 Environmental precautions

Do not empty into drains or the aquatic environment. Cover drains. Clean contaminated objects and areas thoroughly observing environmental regulations. In case of gas being released or leakage into waters, ground or the drainage

system, the appropriate authorities must be informed.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Remove mechanically, placing in appropriate containers for disposal.

6.4 References to other sections

Personal protection equipment refer to chapter 8.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Wear protective clothing. Close container tightly once it is no longer in use. Store away from direct sunlight, heat, spark, fire and other sources of ignition. Empty containers may still contain mixed or unmixed materials, which may be hazardous.

7.2 Storage

Keep in closed, original container. Store container in a cool, dry and ventilated area. Protect from direct sunlight and heat or heating elements. Do not store near spark, fire and other sources of ignition. Keep away from food, beverages and animal feed. Keep away from oxidizing agents. Protect from frost, humidity and heat.

SECTION 8: Exposure Controls/Personal Protection

8.1 Exposure Limits & Controls

OSHA

No limit values from OSHA. Use in a well-ventilated area.

Skin Protection

Use protective clothing to prevent skin contact. Wear nitrile or butyl rubber gloves. Ensure the chemical resistance of the gloves is suitable for use with these chemicals.

Eye Protection

Wear tight-fitting, protective goggles or face shield.

Respiratory Protection

When applying material in confined spaces, use appropriate NIOSH mask. When applying in vented spaces, respiratory protection is not required unless there are sensitivities to chemicals listed in MSDS.

Body Protection

For protection against direct skin contact, ensure protective clothing covers all exposed skin areas.

General Protection & Hygiene

Avoid contact with skin, eyes and clothing. In case of skin sensitivity, protect skin with protective skin cream. Remove contaminated clothing immediately. Do not eat, drink or smoke in or around application area. Wash hands before taking breaks and at the end of application.

SECTION 9: Physical and Chemical Properties

Physical State:	Liquid
Color:	Transparent
Odor:	Low

PH-Value: No Data Available

Changes in physical state

Melting point No Data Available

Initial Boiling point and boiling range No Data Available

Sublimation point No Data Available

Softening point No Data Available

Pour Point No Data Available

Flash point: > 142 °F

Flammability

Solid No Data Available

Gas No Data Available

Lower explosion limits No Data Available

Upper explosion limits No Data Available

Ignition temperature No Data Available

Auto-ignition temperature

Solid No Data Available

Gas No Data Available

Decompression Temperature No Data Available

Vapor Pressure No Data Available

Density at 73 °F ~0.9 g/cm³

Partition coefficient: No Data Available

Viscosity/Dynamic (at 73 °F) ~50 CPS

Viscosity/Kinematic No Data Available

Flow Time No Data Available

Vapor Density No Data Available

Evaporation Rate No Data Available

SECTION 10: Stability and Reactivity

10.1 Reactivity

No dangerous reactions by handling and stock-keeping according to the guidelines.

10.2 Chemical Stability

No decomposition if used according to guidelines.

10.3 Possibility of hazardous reactions

No Data Available

10.4 Conditions to avoid

No Data Available

10.5 Incompatible materials

No Data Available

10.6 Hazardous decomposition products

No Data Available

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or in contact with skin.

ATEmix calculated

ATE (oral) 1312,9 mg/kg; ATE (dermal) 1540,2 mg/kg

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	LD50	1030 mg/kg	Rat	
	dermal	ATE	1100 mg/kg		
	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>5000 mg/kg	Rabbit	
100-51-6	benzyl alcohol				
	oral	LD50	1230 mg/kg	Rat	GESTIS
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		
90-72-2	2,4,6-Tris-(dimethylaminomethyl)phenol				
	oral	LD50	1670 mg/kg	Rat	
	dermal	LD50	1242 mg/kg	Rabbit	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitizing effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine), (2,4,6-Tris-(dimethylaminomethyl)phenol)

May cause heavy allergic reactions with chronic effects after a sensitization and a later exposure by very low amounts.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Observations relevant to classification

Sensitization/Irritant effect on the respiratory tract: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SECTION 12: Ecological Information

12.1 Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50	110 mg/l	96 h	Leuciscus idus (golden orfe)	

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	benzyl alcohol	1,05

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the criteria for classification as PBT or vPvB.

Further Information

Harmful to aquatic life with long lasting effects. Do not empty into drains or the aquatic environment.

SECTION 13: Disposal Considerations

13.1 Product Disposal

Containers that have been completely emptied may be recycled per federal, state and local regulations and disposal guidelines. Containers that have not been emptied or contain product residue may still contain hazardous materials and should be disposed of in accordance with federal, state and local regulations regarding hazardous material disposal.

SECTION 14: Transportation Information

Land transport (ADR/RID)

- 14.1. UN number: UN 2735
- 14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine)
- 14.3. Transport hazard class(es): 8
- 14.4. Packing group: III
- Hazard label: 8
- Classification code: C7
- Special Provisions: 274
- Limited quantity: 5 L
- Transport category: 3
- Hazard No: 80
- Tunnel restriction code: E

Other applicable information (land transport)

E1

Inland waterways transport (ADN)

14.1. UN number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Classification code: C7
Special Provisions: 274
Limited quantity: 5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Marine pollutant: no
Special Provisions: 223, 274
Limited quantity: 5 L
EmS: F-A, S-B

Other applicable information (marine transport)

E1

Air transport (ICAO)

14.1. UN number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Isophoronediamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8
Special Provisions: A3 A803
Limited quantity Passenger: 1 L
IATA-packing instructions - Passenger: 852
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 856
IATA-max. quantity -Cargo: 60 L

Other applicable information (air transport)

E1

: Y841

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory Information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other Information**Relevant R-phrases (Number and full text)**

20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
21/22	Harmful in contact with skin and if swallowed.
34	Causes burns.
43	May cause sensitization by skin contact.
52	Harmful to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.

Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H302+H312	Harmful if swallowed or in contact with skin.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data on this MSDS relate only to the specific material designated herein. We do not assume any liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.